


Plan



Section A-A'

CENTER OPENING
EXPANSION LINES

SPECIFICATIONS

- Material will be high quality 100% recycled grey iron; ASTM A48 class 35b or better; hardness 170-223 brinnell (unless specified otherwise; see below).

Material:

- Grey iron ASTM A48 (standard)
- Aluminum, ASTM B26
- Ductile iron, (required for all load ratings higher than pedestrian) ASTM A536 class 65-45-12.
- Nickel bronze (ASTM B30)
- Bronze (ASTM B26)

- Finish will be natural patina of raw iron (unless specified otherwise; see below).

Finish:

- Raw (standard)
- Rust conditioner
- Polyester Powder Coat*
- Liquid Coat (wet paint)*
- Color:
 - *Please specify standard UA color or mfr. name and color code.
- Brush (bronze/nickel/aluminum only)
- Polish (bronze/nickel/aluminum only)
- Galvanized (grey iron and ductile iron only)
- Other:

- Dimensions are nominal.

Notes

- 1) Cast in four pieces.
- 2) Grate is 1 1/4" thick at edge.
- 3) Center opening expansions at 3 1/4" increments
- 4) No openings greater than 3/8", in conformance with ADA Accessibility Guidelines.

Comments:

Tree Grate

8' Rd. Flat Rainbow

Page: 1 of 1 Date: 5/22/13



465 E. FIFTEENTH ST. sales@urbanaccessories.com
TACOMA, WA 98421 www.urbanaccessories.com
(877) 487-0488