



Plan

3/4" THICK
SOLID GRATE



CENTER OPENING
EXPANSION LINES

Section A-A'

SPECIFICATIONS

- Material will be high quality 100% grey iron; ASTM A48 class 35b or better; hardness 170-223 brinnell (unless specified otherwise; see below).

Material:

- Grey iron ASTM A48 (standard)
- Aluminum, ASTM B26
- Ductile iron, (required for all load ratings higher than pedestrian) ASTM A536 class 65-45-12.
- Nickel bronze (ASTM B30)
- Bronze (ASTM B26)

- Finish will be natural patina of raw steel (unless specified otherwise; see below).

Finish:

- Raw (standard)
- Polyester Powder Coat*
- Liquid Coat (wet paint)*
Color:
*Please specify standard UC color or mfr. name and color code.
- Brush (bronze/nickel/aluminum only)
- Polish (bronze/nickel/aluminum only)
- Galvanized (grey iron and ductile iron only)
- Other:

- **Dimensions are nominal.**

Notes

- 1) Cast in four pieces.
- 2) Grate is 3/4" thick at edge.
- 3) Center opening expansions at 1'-10" and 2'-4" diameter.
- 4) Grate weighs 292 lbs.

Comments:

Tree Grate

5' Rd. Standard Flat

Page 1 of 1 Date: 5/30/12



465 E. FIFTEENTH ST. sales@urbanaccessories.com
TACOMA, WA 98421 www.urbanaccessories.com
(877) 487-0488