

Plan

TYP. 7/8" OPENINGS AT TOP OF GRATE

Section A-A'

3/4" THICK _ SOLID GRATING

SPECIFICATIONS

Material will be high quality 100% recycled grey iron; ASTM A48 class 35b or better; hardness 170-223 brinnell (unless specified otherwise; see below).

Material:

- ☐ Grey iron ASTM A48 (standard)
- □ Aluminum, ASTM B26
- □ Ductile iron, (required for all load ratings higher than pedestrian) ASTM A536 class 65-45-12.
- □ Nickel bronze (ASTM B30)
- □ Bronze (ASTM B26)
- Finish will be natural patina of raw iron (unless specified otherwise; see below).

 Finish:

- □ Raw (standard)
- □ Rust conditioner
- □ Polyester Powder Coat*
- □ Liquid Coat (wet paint)* Color:
- *Please specify standard UA color or mfr. name and color code.
- ☐ Brush (bronze/nickel/aluminum only)
- □ Polish (bronze/nickel/aluminum only)
- □ Galvanized (grey iron and ductile iron only)
- □ Other:

Dimensions are nominal.

- 1) Grate is $\frac{3}{4}$ " thick at edge.
- 2) 154.4 sq. in. open area per grate.
 3) Grate weighs 66.5 lbs.

Comments:

Drain Grate

24" Sq. Grid

Page 1 of 1 Date: 4/16/12



465 E. FIFTEENTH ST. sales@urbanaccessories.com TACOMA, WA 98421 www.urbanaccessories.com (877) 487-0488