

$\frac{7}{16}$ " TYP. 1/8" DEPRESSIONS

Section A-A'

 $1\frac{1}{4}$ " THICK

AT EDGE

SPECIFICATIONS

Material will be high quality 100% recycled grey iron; ASTM A48 class 35b or better; hardness 170-223 brinnell (unless specified otherwise; see below).

Material:

- ☐ Grey iron ASTM A48 (standard)
- □ Aluminum, ASTM B26
- □ Ductile iron, (required for all load ratings higher than pedestrian) ASTM A536 class 65-45-12.
- □ Nickel bronze (ASTM B30)
- □ Bronze (ASTM B26)
- Finish will be natural patina of raw iron (unless specified otherwise; see below).

 Finish:

- □ Raw (standard)
- □ Rust conditioner
- □ Polyester Powder Coat*
- □ Liquid Coat (wet paint)* Color:
- *Please specify standard UA color or mfr. name and color code.
- ☐ Brush (bronze/nickel/aluminum only)
- □ Polish (bronze/nickel/aluminum only)
- □ Galvanized (grey iron and ductile iron only)
- □ Other:

- Dimensions are nominal.

- 1) Cast in one piece.
- 2) Grate is 1- 1/4" thick at edge.
- 3) Depressions are no wider than ½", with single step-downs no deeper than 1/4", in conformance with ADA Accessibility Guidelines.

Comments:

Manhole Cover

32" Rd. Double Wave

Page 1 of 1 Date: 4/16/12



465 E. FIFTEENTH ST. sales@urbanaccessories.com TACOMA, WA 98421 www.urbanaccessories.com (877) 487-0488